

# presents **ULTRACOVER®**

## Advantages

- Ultra-light and silky-soft texture
- Very high tear and tear propagation resistance with 150/140 daN / 5 cm at 200 gr / m<sup>2</sup>
- Nano-top coating against capillary formation
- High flexibility & UV resistance
- Anti-fungicide equipment & dirt resistance
- Low storage volume
- 5 year warranty
- Swiss made with Ökotex standard 100

## Application

- Persenning
- Awning
- Covers
- Especially for outdoor use

## Technical data

Coating	Silikon	one-sided
Support material	PES	80 dtex PES HT
Weight	210 gr / m <sup>2</sup>	EN ISO - 2286-2
Width	183 cm	
Standard roll length	30 m	
Tear resistance	150 / 140 daN / 5 cm	EN ISO - 1421
Extra tear resistance	20 / 20 daN	DIN 53.363
Color- & Lightfastness	≥ 7 (Xenotest 750 h)	ISO 105-B02
UV-filtering	UPF 50 +	NFEN 13758-1+A1
Use temperature	- 50°C / +120°C	
Thickness	> 700 cm	EN 20811
Mildew resistance	Grad 0, excellent	EN ISO 846-A
Water column	> 400	EN 20811
Guarantee	5 Years	



**Width: 183 cm**  
**Weight: 200 gr / m<sup>2</sup>**



The specified technical data are mean values. Deviations are possible. Production changes reserved. The presentation of our products is informal information that may change.

The colors of the pictures are not binding.

perlgrau / pearl grey

**Simulation**